

Esempi di Programmazione Haskell

Marco Comini

3 gennaio 2008

In questo scritto intendo mostrare alcuni semplici esempi di programmi in Haskell per iniziare ad impratichirsi con il linguaggio più alcuni esempi completi di Strutture Dati Astratte sviluppate cercando di sfruttare appieno le caratteristiche di polimorfismo隐式 e del meccanismo delle classi.

Questo è un work in progress che non pretende ne di essere esauriente ne tantomeno esaustivo.

1 Esempietti

1.1 Numeri e Liste

1. In questo esempio generiamo la lista dei primi numeri primi minori di n , con un algoritmo non troppo efficiente ma molto semplice da scrivere.

```
eratostene n = 1:era [2..n]
  where
    era [] = []
    era (x:xs)
      | x*x < n = era ys
      | otherwise = ys
    where
      ys = filter (\y->y `rem` x /= 0) xs
```

si noti come nello scope del where è visibile la n del pattern di definizione.

2. In questo esempio voglio mostrare una variante dell'algoritmo di *counting sort* che non ha bisogno di sapere a priori il massimo e il minimo dei valori da ordinare. Come nell'algoritmo originale abbiamo una fase in cui vogliamo accumulare il numero di occorrenze di ogni numero da ordinare. Invece di usare un vettore utilizziamo una funzione che dato un certo valore ci restituirà il numero di occorrenze di detto valore. Man mano leggiamo la lista aggiorniamo tale funzione nonchè il massimo e il minimo valore incontrato in modo da poter ricostruire poi la lista ordinata.

```
countsrt :: (Enum a, Ord a) => [a] -> [a]
countsrt [] = []
countsrt xs@(x:_)= cnt2list [] list2cnt
  where
    list2cnt = foldl aggr (x,x,\_>0) xs
    where
      aggr (a,b,f) n = (min a n,max b n,
                           \i -> if i == n then 1+f n else f i)
    cnt2list xs (a,b,f)
```

```

| a > b      = xs
| otherwise = cnt2list (put (f b) xs) (a, pred b, f)
where
  put 0 ys = ys
  put n ys = b : put (n-1) ys

```

chiaramente questo algoritmo sarà tanto più inefficiente quanto meno è “densa” la distribuzione dei valori all’interno del range minimo–massimo.

1.2 Alberi

Si definiscano gli Alberi Binari di Ricerca col seguente tipo di dato astratto (polimorfo)

```
data (Ord a, Show a, Read a) => BST a = Void | Node a (BST a) (BST a)
deriving (Eq, Ord, Read, Show)
```

e si usi (per comodità) lo stesso tipo di dato anche per Alberi Binari normali.

1. Iniziamo con un esempio facile per calcolare l’altezza di un albero (dove non uso volutamente nessun tipo di fold, per quello si vedano gli esercizi).

```
treeheight Void = 0
treeheight (Node y l r) = 1 + max (treeheight l) (treeheight r)
```

2. Ora vediamo come “potare” un albero ad una certa profondità.

```
takedepth 0 _ = Void
takedepth _ Void = Void
takedepth n (Node y l r) = Node y (takedepth (n-1) l) (takedepth (n-1) r)
```

1.3 Matrici

Implementiamo le matrici si implementano come liste di liste, per righe. Quindi

$$\begin{pmatrix} 1 & 2 & 3 & 4 \\ 5 & 6 & 7 & 8 \\ 9 & 10 & 11 & 12 \end{pmatrix}$$

verrà codificata come

```
[ [1, 2, 3, 4],
  [5, 6, 7, 8],
  [9, 10, 11, 12]]
```

2 Binary (Search) Trees

2.1 BinaryTrees.hs

Qui l’interessante è la definizione delle istanze di **Show** e **Read** oltre che la definizione di una **fold** su alberi che può essere usata, come per le fold su liste, per fare moltissime cose.

Si veda la **toList**.

```

module BinaryTrees(Tree(..) ,
empty ,
fold ,
isEmpty ,
new ,
toList) where

data Tree a = Void | Node a (Tree a) (Tree a) — deriving (Eq)

instance Show a => Show (Tree a)
where
  showsPrec _ = showsTree
  where
    — showsTree :: Show a => Tree a -> ShowS
    showsTree Void = (',':)
    showsTree (Node x l r) = ('<':) . showsTree l .
    (',' :) . shows x .
    (',' :) . showsTree r .
    ('>':)

instance Read a => Read (Tree a)
where
  readsPrec _ = readsTree
  where
    readsTree :: Read a => ReadS (Tree a)
    readsTree ts = [(Node x l r, zs++ys) | ((<':rs), us) <- lex ts,
    (l, vs) <- readsTree (rs++us),
    (x, ws) <- reads vs,
    (r, xs) <- readsTree ws,
    ((>':zs), ys) <- lex xs ]
    ++
    [(Void, rs++us) | (',':rs), us) <- lex ts]

— Exported functions

empty :: Tree a
empty = Void

isEmpty :: Tree a -> Bool
isEmpty Void = True
isEmpty _ = False
— if Eq a then isEmpty = (Void==)

new :: a -> Tree a -> Tree a -> Tree a
— new x l r = (Node x l r)
new = Node

fold :: (a -> b -> b -> b) -> b -> Tree a -> b
fold _ z Void = z
fold f z (Node x l r) = f x (fold f z l) (fold f z r)

toList :: Tree a -> [a]
toList t = fold aggr id t []
where
  — aggr :: a -> ([a]->[a]) -> ([a]->[a]) -> ([a] -> [a])
  aggr x lacc racc = lacc . (x:) . racc

— Not exported functions

sum = fold (\x y z->x+y+z) 0
filteredSum p = fold filteredsum 0

```

```

where
  filteredsum x y z
  | p x      = x + y + z
  | otherwise = y + z

```

2.2 BinarySearchTrees.hs

Qui si mostra come riutilizzare un altro ADT (Abstract Data Type) per implementarne uno nuovo, esportando metodi del vecchio (eventualmente cambiando i nomi) e/o aggiungendo nuovi metodi.

```

module BinarySearchTrees(BST,
  elem,
  empty,
  fold,
  fromList,
  fromListUnique,
  insert,
  insertUnique,
  isEmpty,
  join,
  joinUnique,
  meet,
  sort,
  toList) where

import Prelude hiding (elem)
import BinaryTrees(Tree(..))
import qualified BinaryTrees as BT

type BST a = Tree a
-- Exported functions

empty :: Ord a => BST a
empty = BT.empty

isEmpty :: Ord a => BST a -> Bool
isEmpty = BT.isEmpty

fold :: Ord a => (a -> b -> b -> b) -> b -> BST a -> b
fold = BT.fold

toList :: Ord a => BST a -> [a]
toList = BT.toList

elem :: (Ord a) => a -> BST a -> Bool
elem x Void = False
elem x (Node y l r)
| x == y    = True
| x < y    = elem x l
| otherwise = elem x r

insert :: (Ord a) => a -> BST a -> BST a
insert x Void = Node x Void Void
insert x (Node y l r)
| x <= y   = Node y (insert x l) r
| otherwise = Node y l (insert x r)

```

```

insertUnique      :: (Ord a) => a -> BST a -> BST a
insertUnique x Void = Node x Void Void
insertUnique x n@(Node y l r)
| x==y      = n
| x<y      = Node y (insertUnique x l) r
| otherwise = Node y l (insertUnique x r)

fromList :: Ord a => [a] -> BST a
fromList = foldl (flip insert) Void

fromListUnique :: Ord a => [a] -> BST a
fromListUnique = foldl (flip insertUnique) Void

sort :: Ord a => [a] -> [a]
sort = toList . fromList

join      :: (Ord a) => BST a -> BST a -> BST a
join t1 t2 = fold aggr id t2 t1
  where
    — aggr :: (Ord a) => a -> (BST a -> BST a) -> (BST a -> BST a) -> BST a
    —> BST a
    aggr x lacc racc = lacc . insert x . racc

joinUnique      :: (Ord a) => BST a -> BST a -> BST a
joinUnique t1 t2 = fold aggr id t2 t1
  where
    aggr x lacc racc = lacc . insertUnique x . racc

meet      :: (Ord a) => BST a -> BST a -> BST a
meet t1 t2 = fromList $ meetlist (toList t1) (toList t2)
  where
    meetlist [] _ = []
    meetlist _ [] = []
    meetlist as@(x:xs) bs@(y:ys)
    | x==y      = x : meetlist xs ys
    | x<y      = meetlist xs bs
    | otherwise = meetlist as ys

```

3 Red Black Trees

Invece di implementare i Red Black Trees scegliendo un qualche metodo di default su quando e come inserire elementi, in questa implementazione si va a estendere la classe `Ord` con dei metodi che vadano a specificare cosa fare nei vari casi. In questo modo, con opportune istanze dei metodi si possono ottenere comportamenti molto diversi mantenendo lo stesso codice. Tutti gli esempi su Insiemi, Multinsiemi e Tabelle Associative nel seguito sono proprio istanze opportune di Red Black Trees.

Qui l'interessante è la definizione di due tipi di `map`. Se la funzione f che vogliamo applicare agli elementi di un RBT è monotona (rispetto agli ordini delle istanze di `Ord`) allora possiamo andare a rimpiazzare le immagini via f in place, altrimenti il nuovo albero va interamente ricostruito.

La funzione di ricerca qui potrebbe dover restituire diversi elementi e quindi restituisce una lista.

```

module RedBlackTrees(RBT(),
  Ord'(insEq, valJoin, valMeet),
  empty,

```

```

isEmpty ,
fold ,
lookup ,
toList ,
update ,
join ,
fromList ,
sort ,
meet ,
mapMonotone ,
map ,
delete ,
diff ,
findMin ,
findMax) where

import Prelude hiding (lookup,map)

— The colors of a node in a red-black tree.
data Color = Red | Black | DoublyBlack deriving (Eq, Ord)

instance Show Color where
  show Red   = "r"
  show Black = "b"
  show DoublyBlack = "B"

instance Read Color where
  readsPrec _ = readsColor
  where
    readsColor (' ':xs) = readsColor xs
    readsColor ('\t':xs) = readsColor xs
    readsColor ('\n':xs) = readsColor xs
    readsColor ('b':xs) = [(Black, xs)]
    readsColor ('B':xs) = [(DoublyBlack, xs)]
    readsColor ('r':xs) = [(Red, xs)]
    readsColor (x:xs) = [(error ("undefined_color_'" ++ x ++ "'"), xs)]
    readsColor [] = []

class (Ord a) => Ord' a
  where
    insEq :: a -> a -> Bool
    valJoin, valMeet :: a -> a -> a

    — we assume that ‘insEq’ implies (==)
    insEq = (==)

    valJoin x _ = x

    valMeet x _ = x

— The structure of red-black trees.
data (Ord' a) => RBT a = Node Color a (RBT a) (RBT a) | Void
  deriving (Eq, Ord)

instance (Show a, Ord' a) => Show (RBT a)
  where
    showsPrec _ = showsTree
    where
      — showsTree          :: (Show a, Ord' a) => RBT a -> ShowS
      showsTree Void           = ('.' :')

```

```

showsTree (Node c x l r) = ( '( ':) .
                           showsTree l . ( ' ' :) .
                           shows x . ( ': ':) . shows c . ( ' ' :) .
                           showsTree r .
                           ( ') ':)

instance (Read a, Ord' a) => Read (RBT a)
where
  readsPrec _ = readsTree
  where
    — readsTree :: (Read a, Ord' a) => ReadS (RBT a)
    readsTree ts = [(Node c x l r, qs) | ("(", us) <- lex ts,
                                             (l, vs) <- readsTree us,
                                             (x, ws) <- reads vs,
                                             (" :", xs) <- lex ws,
                                             (c, ys) <- reads xs,
                                             (r, zs) <- readsTree ys,
                                             (")", qs) <- lex zs ]
    ++
    [(Void, rs++us) | (('.':rs), us) <- lex ts]

empty :: (Ord' a) => RBT a
empty = Void

isEmpty :: (Ord' a) => RBT a -> Bool
isEmpty Void = True
isEmpty _ = False

fold :: (Ord' a) => (a -> b -> b -> b) -> b -> RBT a -> b
fold _ z Void = z
fold f z (Node _ x l r) = f x (fold f z l) (fold f z r)

— in the following function we can see how the potential differences
— between == and `insEq` do interact, since we cannot assume that in case
— of equality we can just return (y:xs)

— there can be more than one match
lookup :: (Ord' a) => a -> RBT a -> [a]
lookup x t = fold aggr id t []
where
  aggr y lacc racc
  | y == x = lacc . (y:) . racc
  | x < y = lacc
  | y < x = racc
  — | otherwise = error "RedBlackTrees.lookup: internal error" — lacc (
    racc xs)

toList :: (Ord' a) => RBT a -> [a]
toList t = fold aggr id t []
where
  aggr x lacc racc = lacc . (x:) . racc

update :: (Ord' a) => a -> RBT a -> RBT a
update x t = let (Node _ x2 l r) = upd t
            in Node Black x2 l r
where
  upd Void = Node Red x Void Void
  upd (Node c x2 l r)
  | x `insEq` x2 = (Node c (x `valJoin` x2) l r)
  | x < x2 = balanceL (Node c x2 (upd l) r)
  | otherwise = balanceR (Node c x2 l (upd r))

```

```

join      :: (Ord' a) => RBT a -> RBT a -> RBT a
join t1 t2 = fold aggr id t2 t1
  where
    — aggr :: (Ord' a) => a -> (RBT a -> RBT a) -> (RBT a -> RBT a) -> RBT a
    —> RBT a
    aggr x lacc racc = lacc . update x . racc

fromList :: (Ord' a) => [a] -> RBT a
fromList = foldl (flip update) Void

sort :: (Ord' a) => [a] -> [a]
sort = toList . fromList

meet      :: (Ord' a) => RBT a -> RBT a -> RBT a
meet t1 t2 = fromList$meetlist (toList t1) (toList t2)
  where
    meetlist [] _ = []
    meetlist _ [] = []
    meetlist as@(x:xs) bs@(y:ys)
      | x == y     = (x `valMeet` y):meetlist xs ys
      | x < y      = meetlist xs bs
      | otherwise   = meetlist as ys

    — if function is monotone then the tree structure is preserved thus we can
    — apply the function directly in node values (cannot use fold cause it loses
    — color)

mapMonotone :: (Ord' a, Ord' b) => (a -> b) -> RBT a -> RBT b
mapMonotone _ Void = Void
mapMonotone f (Node c x l r) = Node c (f x) (map f l) (map f r)
  — otherwise we have to reconstruct a new tree entirely

map :: (Ord' a, Ord' b) => (a -> b) -> RBT a -> RBT b
map f t = fold aggr id t Void
  where
    aggr x lacc racc = racc . update (f x) . lacc

delete :: (Ord' a) => a -> RBT a -> RBT a
delete x t = blackenRoot $ deleteTree x t
  where
    blackenRoot Void = Void
    blackenRoot (Node _ x l r) = Node Black x l r

    deleteTree _ Void = Void — no error for non existence
    deleteTree e (Node c e2 l r)
      | e == e2 = if l==Void then addColor c r else
                  if r==Void then addColor c l
                  else let el = rightMost l
                        in delBalanceL (Node c el (deleteTree
                           el l) r)
      | e < e2   = delBalanceL (Node c e2 (deleteTree e l) r)
      | otherwise = delBalanceR (Node c e2 l (deleteTree e r))

  where
    addColor Red tree = tree
    addColor Black Void = Void
    addColor Black (Node Red x lx rx) = Node Black x lx rx
    addColor Black (Node Black x lx rx) = Node DoublyBlack x lx rx

    rightMost (Node _ x _ rx) = if rx==Void then x else rightMost rx
    rightMost Void           = error "internal_error_on_function_delete"

```

```

diff      :: (Ord' a) => RBT a -> RBT a -> RBT a
diff t1 t2 = fold aggr id t1 t2
where
  aggr x lacc racc = lacc . delete x . racc

{-
- findMin          :: (Ord' a) => RBT a -> a
- findMin (Node _ x Void _) = x
- findMin (Node _ _ l _)    = findMin l
- findMin Void         = error "RedBlackTrees.findMin: empty tree has no
                           minimal element"
-
- findMax          :: (Ord' a) => RBT a -> a
- findMax (Node _ x _ Void) = x
- findMax (Node _ _ _ r)    = findMax r
- findMax Void         = error "RedBlackTrees.findMax: empty tree has no
                           maximal element"
-}

findMin :: (Ord' a) => RBT a -> Maybe a
findMin = fold aggr Nothing
where
  aggr x Nothing _ = Just x
  aggr _ 1           = 1

findMax :: (Ord' a) => RBT a -> Maybe a
findMax = fold aggr Nothing
where
  aggr x _ Nothing = Just x
  aggr _ _ 1         = 1

—— Not exported

isBlack          :: (Ord' a) => RBT a -> Bool
isBlack Void        = True
isBlack (Node c _ _ _) = c==Black

isRed            :: (Ord' a) => RBT a -> Bool
isRed Void        = False
isRed (Node c _ _ _) = c==Red

isDoublyBlack     :: (Ord' a) => RBT a -> Bool
isDoublyBlack Void        = True
isDoublyBlack (Node c _ _ _) = c==DoublyBlack

left             :: (Ord' a) => RBT a -> RBT a
left (Node _ _ 1 _) = 1
left _           = error "RedBlackTrees.left:_empty_tree_has_no_left_son"

right            :: (Ord' a) => RBT a -> RBT a
right (Node _ _ _ r) = r
right _           = error "RedBlackTrees.right:_empty_tree_has_no_right_son"

singleBlack       :: (Ord' a) => RBT a -> RBT a
singleBlack Void        = Void
singleBlack (Node DoublyBlack x 1 r) = Node Black x 1 r
singleBlack _       = error "RedBlackTrees.singleBlack:_internal_error"

—— for the implementation of balanceL and balanceR refer to picture 3.5, page

```

```

27,
— Okasaki "Purely Functional Data Structures"
balanceL :: (Ord' a) => RBT a -> RBT a
balanceL tree
| isRed leftTree && isRed (left leftTree)
= let Node _ z (Node _ y (Node _ x a b) c) d = tree
  in Node Red y (Node Black x a b) (Node Black z c d)

| isRed leftTree && isRed (right leftTree)
= let Node _ z (Node _ x a (Node _ y b c)) d = tree
  in Node Red y (Node Black x a b) (Node Black z c d)

| otherwise
= tree

where
  leftTree = left tree

balanceR :: (Ord' a) => RBT a -> RBT a
balanceR tree
| isRed rightTree && isRed (right rightTree)
= let Node _ x a (Node _ y b (Node _ z c d)) = tree
  in Node Red y (Node Black x a b) (Node Black z c d)

| isRed rightTree && isRed (left rightTree)
= let Node _ x a (Node _ z (Node _ y b c) d) = tree
  in Node Red y (Node Black x a b) (Node Black z c d)

| otherwise
= tree

where
  rightTree = right tree

— balancing after deletion

delBalanceL :: (Ord' a) => RBT a -> RBT a
delBalanceL tree
| isDoublyBlack (left tree) = reviseLeft tree
| otherwise = tree
where
  reviseLeft tree
  | r==Void
    = tree
  | isblackr && isRed (left r)
    = let Node col x a (Node _ z (Node _ y b c) d) = tree
      in Node col y (Node Black x (singleBlack a) b) (Node Black z c d)
  | isblackr && isRed (right r)
    = let Node col x a (Node _ y b (Node _ z c d)) = tree
      in Node col y (Node Black x (singleBlack a) b) (Node Black z c d)
  | isblackr
    = let Node col x a (Node _ y b c) = tree
      in Node (if col==Red then Black else DoublyBlack) x (singleBlack a) (
        Node Red y b c)
  | otherwise
    = let Node _ x a (Node _ y b c) = tree
      in Node Black y (reviseLeft (Node Red x a b)) c
where
  r = right tree
  isblackr = isBlack r

```

```

delBalanceR :: (Ord' a) => RBT a -> RBT a
delBalanceR tree
| isDoublyBlack (right tree) = reviseRight tree
| otherwise = tree
where
  reviseRight tree
    | l==Void = tree
    | isblackl && isRed (left l)
      = let Node col x (Node _ y (Node _ z d c) b) a = tree
        in Node col y (Node Black z d c) (Node Black x b (singleBlack a))
    | isblackl && isRed (right l)
      = let Node col x (Node _ z d (Node _ y c b)) a = tree
        in Node col y (Node Black z d c) (Node Black x b (singleBlack a))
    | isblackl
      = let Node col x (Node _ y c b) a = tree
        in Node (if col==Red then Black else DoublyBlack) x (Node Red y c b)
          (singleBlack a)
    | otherwise
      = let Node _ x (Node _ y c b) a = tree
        in Node Black y c (reviseRight (Node Red x b a))
  where
    l = left tree
    isblackl = isBlack l

```

4 Sets e MultiSets

4.1 Sets.hs

Qui l'interessante per prima cosa è la definizione del tipo Set a con le varie istanze per usare opportunamente RBT, oltre che l'istanza **Eq** (Set a).

Inoltre è interessante la ri-definizione delle istanze di **Show** e **Read** che andremmo a ereditare da RBT. Una nota d'attenzione merita l'accorgimento per mettere il giusto numero di , fra gli elementi di un insieme.

Svariati metodi di RBT vengono nascosti mentre molte operazioni tipiche degli insiemi vengono introdotte mediante opportune **fold**.

```

module Sets(Set ,
  (\`),
  delete ,
  difference ,
  elem ,
  empty ,
  filter ,
  findMax ,
  findMin ,
  fold ,
  fromList ,
  insert ,
  intersection ,
  intersections ,
  isEmpty ,
  isProperSubsetOf ,
  isSubsetOf ,
  map ,
  mapMonotone ,
  singleton ,
  size ,
  toList ,
  union ,

```

```

unions) where

import qualified RedBlackTrees as RBT
import RedBlackTrees(RBT,Ord')
import Prelude hiding (
    elem,
    filter,
    lookup,
    map,
    sum)

newtype (Ord a) => Val a = SetValue a deriving (Eq,Ord)
instance (Ord a) => Ord' (Val a)
instance (Ord a, Show a) => Show (Val a)
where
    showsPrec _ (SetValue x) = shows x
instance (Ord a, Read a) => Read (Val a)
where
    readsPrec _ xs = [ (SetValue x, ys) | (x,ys)<-reads xs ]
newtype Set a = MakeSet (RBT (Val a))
instance (Ord a) => Eq (Set a)
where
    x == y = toList x == toList y
instance (Ord a, Show a) => Show (Set a)
where
    showsPrec _ (MakeSet t) = ('{':) . (RBT.fold aggr id t) . (end:)
    where
        end = '}'
    -- aggr :: Show a => a -> ShowS -> ShowS -> ShowS
    aggr x lacc racc = lacc . shows x . comma racc
    -- comma :: ShowS -> ShowS
    comma shws xs = if head ys == end then ys else (',':ys)
    where ys = shws xs
instance (Ord a, Read a) => Read (Set a)
where
    readsPrec _ = readsSet
    where
        readsSet ts = [ (MakeSet t, vs) | ("{", us)<-lex ts,
            (t, vs)<-readl us]
        readl ts = [ (RBT.empty, us) | ("}", us)<-lex ts ] ++
            [ (RBT.update x s, vs) | (x, us)<-reads ts,
            (s, vs)<-readl' us]
        readl' ts = [ (RBT.empty, us) | ("}", us)<-lex ts ] ++
            [ (RBT.update x s, ws) | (",", us)<-lex ts,
            (x, vs)<-reads us,
            (s, ws)<-readl' vs]
-- Exported functions

```

```

empty :: Ord a => Set a
empty = MakeSet RBT.empty

isEmpty :: (Ord a) => Set a -> Bool
isEmpty (MakeSet t) = RBT.isEmpty t

elem :: (Ord a) => a -> Set a -> Bool
x `elem` (MakeSet t) = RBT.lookup (SetValue x) t /= []

size :: Ord a => Set a -> Integer
size (MakeSet t) = RBT.fold count 0 t
  where
    count _ y z = 1+y+z

insert :: (Ord a) => a -> Set a -> Set a
insert x (MakeSet t) = MakeSet (RBT.update (SetValue x) t)

singleton :: (Ord a) => a -> Set a
singleton x = insert x empty

delete :: Ord a => a -> Set a -> Set a
delete x (MakeSet t) = MakeSet (RBT.delete (SetValue x) t)

fromList :: (Ord a) => [a] -> Set a
fromList = MakeSet . (foldl update' RBT.empty)
  where
    update' t x = RBT.update (SetValue x) t

fold :: (Ord a) => (a -> b -> b) -> b -> Set a -> b
fold f z (MakeSet t) = RBT.fold aggr id t z
  where
    aggr (SetValue x) lacc racc = lacc . f x . racc

toList :: (Ord a) => Set a -> [a]
toList = fold (:)

mapMonotone :: (Ord a, Ord b) => (a -> b) -> Set a -> Set b
mapMonotone f (MakeSet t) = MakeSet (RBT.mapMonotone f' t)
  where
    f' (SetValue x) = SetValue (f x)

map :: (Ord a, Ord b) => (a -> b) -> Set a -> Set b
map f (MakeSet t) = MakeSet (RBT.map f' t)
  where
    f' (SetValue x) = SetValue (f x)

union :: (Ord a) => Set a -> Set a -> Set a
union (MakeSet t1) (MakeSet t2) = MakeSet (RBT.join t2 t1)

unions :: (Ord a) => [Set a] -> Set a
unions = foldr union empty

intersection :: (Ord a) => Set a -> Set a -> Set a
intersection (MakeSet t1) (MakeSet t2) = MakeSet (RBT.meet t1 t2)

intersections :: (Ord a) => [Set a] -> Set a
intersections [] = empty
intersections xs = foldr1 intersection xs

difference :: (Ord a) => Set a -> Set a -> Set a

```

```

difference (MakeSet t1) (MakeSet t2) = MakeSet (RBT.diff t2 t1)

infixl 9 \\
(\\) :: (Ord a) => Set a -> Set a -> Set a
(\\) = difference

filter :: Ord a => (a -> Bool) -> Set a -> Set a
filter p = fold insert' empty
  where
    insert' x = if p x then insert x else id

findMin :: Ord a => Set a -> Maybe a
findMin (MakeSet t) = fmap cnv $ RBT.findMin t
  where cnv (SetValue x) = x

findMax :: Ord a => Set a -> Maybe a
findMax (MakeSet t) = fmap cnv $ RBT.findMax t
  where cnv (SetValue x) = x

isSubsetOf :: Ord a => Set a -> Set a -> Bool
x `isSubsetOf` y = isEmpty (x \\ y)

isProperSubsetOf :: Ord a => Set a -> Set a -> Bool
x `isProperSubsetOf` y = x `isSubsetOf` y && (not $ isEmpty $ y \\ x)

--- Not exported functions

sum :: (Num a, Ord a) => Set a -> a
sum = fold (+) 0

{- TO DO
partition :: Ord a => (a -> Bool) -> Set a -> (Set a, Set a)

split :: Ord a => a -> Set a -> (Set a, Set a)
splitMember :: Ord a => a -> Set a -> (Set a, Bool, Set a)

deleteMin :: Set a -> Set a
deleteMax :: Set a -> Set a
deleteFindMin :: Set a -> (a, Set a)
deleteFindMax :: Set a -> (a, Set a)
-}

```

4.2 MultiSets.hs

Questo modulo è praticamente identico al precedente a parte l’istanza **Ord**’ (Val a) che ci obbliga a inserire elementi uguali più volte generando quindi multinsiemi. Ovviamente vale solo come esempio visto che tenere i duplicati è sicuramente il metodo più inefficiente per impelmentare multinsiemi.

```

module MultiSets(MultiSet,
  (\\),
  delete,
  difference,
  elem,
  empty,
  filter,

```

```

findMax ,
findMin ,
fold ,
fromList ,
insert ,
intersection ,
intersections ,
isEmpty ,
isProperSubsetOf ,
isSubsetOf ,
map,
mapMonotone ,
singleton ,
size ,
toList ,
union ,
unions) where

import qualified RedBlackTrees as RBT
import RedBlackTrees(RBT,Ord')
import Prelude hiding (
    elem,
    filter ,
    lookup ,
    map,
    sum)

newtype (Ord a) => Val a = SetValue a deriving (Eq,Ord)

instance (Ord a) => Ord' (Val a)
where
    insEq _ _ = False

instance (Ord a, Show a) => Show (Val a)
where
    showsPrec _ (SetValue x) = shows x

instance (Ord a, Read a) => Read (Val a)
where
    readsPrec _ xs = [ (SetValue x, ys) | (x,ys)<-reads xs ]

newtype MultiSet a = MakeSet (RBT (Val a))

instance (Ord a) => Eq (MultiSet a)
where
    x == y = toList x == toList y

instance (Ord a, Show a) => Show (MultiSet a)
where
    showsPrec _ (MakeSet t) = ( '{':) . (RBT.fold aggr id t) . (end:)
        where
            end = '}'
            aggr x lacc racc = lacc . shows x . comma racc
            comma shws xs = if head ys == end then ys else ( ',':ys)
                where ys = shws xs

instance (Ord a, Read a) => Read (MultiSet a)
where

```

```

readsPrec _ = readsSet
where
  readsSet ts = [ (MakeSet t, vs) | ("{", us) <- lex ts,
                  (t, vs) <- readl us]

  readl ts = [ (RBT.empty, us) | ("}", us) <- lex ts ] ++
              [ (RBT.update x s, vs) | (x, us) <- reads ts,
                (s, vs) <- readl' us]

  readl' ts = [ (RBT.empty, us) | ("}", us) <- lex ts ] ++
              [ (RBT.update x s, ws) | ("," , us) <- lex ts,
                (x, vs) <- reads us,
                (s, ws) <- readl' vs]

type Set a = MultiSet a

— Exported functions

empty :: Ord a => Set a
empty = MakeSet RBT.empty

isEmpty :: (Ord a) => Set a -> Bool
isEmpty (MakeSet t) = RBT.isEmpty t

elem :: (Ord a) => a -> Set a -> Bool
x `elem` (MakeSet t) = RBT.lookup (SetValue x) t /= []

size :: Ord a => Set a -> Integer
size (MakeSet t) = RBT.fold count 0 t
where
  count _ y z = 1+y+z

insert :: (Ord a) => a -> Set a -> Set a
insert x (MakeSet t) = MakeSet (RBT.update (SetValue x) t)

singleton :: (Ord a) => a -> Set a
singleton x = insert x empty

delete :: Ord a => a -> Set a -> Set a
delete x (MakeSet t) = MakeSet (RBT.delete (SetValue x) t)

fromList :: (Ord a) => [a] -> Set a
fromList = MakeSet . (foldl update' RBT.empty)
where
  update' t x = RBT.update (SetValue x) t

fold :: (Ord a) => (a -> b -> b) -> b -> Set a -> b
fold f z (MakeSet t) = RBT.fold aggr id t z
where
  aggr (SetValue x) lacc racc = lacc . f x . racc

toList :: (Ord a) => Set a -> [a]
toList = fold (:)

mapMonotone :: (Ord a, Ord b) => (a -> b) -> Set a -> Set b
mapMonotone f (MakeSet t) = MakeSet (RBT.mapMonotone f' t)
where
  f' (SetValue x) = SetValue (f x)

map :: (Ord a, Ord b) => (a -> b) -> Set a -> Set b

```

```

map f (MakeSet t) = MakeSet (RBT.map f' t)
  where
    f' (SetValue x) = SetValue (f x)

union :: (Ord a) => Set a -> Set a -> Set a
union (MakeSet t1) (MakeSet t2) = MakeSet (RBT.join t2 t1)

unions :: (Ord a) => [Set a] -> Set a
unions = foldr union empty

intersection :: (Ord a) => Set a -> Set a -> Set a
intersection (MakeSet t1) (MakeSet t2) = MakeSet (RBT.meet t1 t2)

intersections :: (Ord a) => [Set a] -> Set a
intersections [] = empty
intersections xs = foldr1 intersection xs

difference :: (Ord a) => Set a -> Set a -> Set a
difference (MakeSet t1) (MakeSet t2) = MakeSet (RBT.diff t2 t1)

infixl 9 \\
(\\\) :: (Ord a) => Set a -> Set a -> Set a
(\\\) = difference

filter :: Ord a => (a -> Bool) -> Set a -> Set a
filter p = fold insert' empty
  where
    insert' x = if p x then insert x else id

findMin :: Ord a => Set a -> Maybe a
findMin (MakeSet t) = fmap cnv $ RBT.findMin t
  where cnv (SetValue x) = x

findMax :: Ord a => Set a -> Maybe a
findMax (MakeSet t) = fmap cnv $ RBT.findMax t
  where cnv (SetValue x) = x

isSubsetOf :: Ord a => Set a -> Set a -> Bool
x `isSubsetOf` y = isEmpty (x \\ y)

isProperSubsetOf :: Ord a => Set a -> Set a -> Bool
x `isProperSubsetOf` y = x `isSubsetOf` y && (not $ isEmpty $ y \\ x)

—— Not exported functions

sum :: (Num a, Ord a) => Set a -> a
sum = fold (+) 0

```

4.3 MultiSetsCompact.hs

Qui implementiamo multinsiemi più astutamente come coppie (valore,numero di ripetizioni). Si vedano le dichiarazioni delle istanze (specialmente **Ord'** (Val a), **Ord** (Val a) e **Show** (Val a)).

```

module MultiSetsCompact(MultiSet,
  (\\\),
  delete,
  difference,
  elem,
  empty,

```

```

filter ,
findMax ,
findMin ,
fold ,
fromList ,
insert ,
intersection ,
intersections ,
isEmpty ,
isProperSubsetOf ,
isSubsetOf ,
map,
mapMonotone ,
singleton ,
size ,
toList ,
union ,
unions) where

import qualified RedBlackTrees as RBT
import RedBlackTrees(RBT,Ord')
import Prelude hiding (
  elem,
  filter ,
  lookup,
  map,
  sum)

data (Ord a) => Val a = MSetVal a Int

instance (Ord a) => Eq (Val a)
where
  (MSetVal x _) == (MSetVal y _) = x == y

instance (Ord a) => Ord (Val a)
where
  compare (MSetVal x _) (MSetVal y _) = compare x y

instance (Ord a) => Ord' (Val a)
where
  valJoin (MSetVal x n) (MSetVal y m)
  | x == y    = MSetVal x (max (n+m) 0)
  | otherwise = error "MultiSets.valJoin:_unjoinable_items"

  valMeet (MSetVal x n) (MSetVal y m)
  | x == y    = MSetVal x (min n m)
  | otherwise = error "MultiSets.valMeet:_unmeetable_items"

instance (Ord a, Show a) => Show (Val a)
where
  showsPrec _ (MSetVal x n) = shows x . if n==1 then id else (':':) . shows
    n

instance (Ord a, Read a) => Read (Val a)
where
  readsPrec _ us = [ (MSetVal x n, xs) | (x,vs) <- reads us ,
    (":",ws) <- lex vs ,
    (n,xs) <- reads ws] ++
  [ (MSetVal x 1, vs) | (x,vs) <- reads us]

```

```

newtype MultiSet a = MakeSet (RBT (Val a))

instance (Ord a) => Eq (MultiSet a)
  where
    x == y = toList x == toList y

instance (Ord a, Show a) => Show (MultiSet a)
  where
    showsPrec _ (MakeSet t) = ('{':) . (RBT.fold aggr id t) . (':end)
      where
        end = '}' ,
        aggr x lacc racc = lacc . shows x . comma racc
        comma shws xs = if head ys == end then ys else (',':ys)
        where ys = shws xs

instance (Ord a, Read a) => Read (MultiSet a)
  where
    readsPrec _ = readsMultiSet
    where
      readsMultiSet ts = [ (MakeSet t, vs) | ("{", us) <- lex ts,
                           (t, vs) <- readl us]
      readl ts = [ (RBT.empty, us) | ("}", us) <- lex ts ] ++
                  [ (RBT.update x s, vs) | (x, us) <- reads ts,
                    (s, vs) <- readl' us]
      readl' ts = [ (RBT.empty, us) | ("}", us) <- lex ts ] ++
                  [ (RBT.update x s, ws) | (",", us) <- lex ts,
                    (x, vs) <- reads us,
                    (s, ws) <- readl' vs]

type Set a = MultiSet a

-- Exported functions

empty :: Ord a => Set a
empty = MakeSet RBT.empty

isEmpty :: (Ord a) => Set a -> Bool
isEmpty (MakeSet t) = RBT.isEmpty t

elem :: (Ord a) => a -> Set a -> Bool
x `elem` (MakeSet t) = RBT.lookup (MSetVal x (error "MultiSetsCompact.lookup: internal_error")) t /= []

size :: Ord a => Set a -> Integer
size (MakeSet t) = RBT.fold count 0 t
  where
    count _ y z = 1+y+z

insert :: (Ord a) => Int -> a -> Set a -> Set a
insert n x (MakeSet t) = MakeSet (RBT.update (MSetVal x n) t)

singleton :: (Ord a) => a -> Set a
singleton x = insert 1 x empty

fromList :: (Ord a) => [a] -> Set a

```

```

fromList = MakeSet . (foldl update' RBT.empty)
 $\text{where}$ 
  update' t x = RBT.update (MSetVal x 1) t

fold :: (Ord a)  $\Rightarrow$  (Int  $\rightarrow$  a  $\rightarrow$  b  $\rightarrow$  b)  $\rightarrow$  b  $\rightarrow$  Set a  $\rightarrow$  b
fold f z (MakeSet t) = RBT.fold aggr id t z
 $\text{where}$ 
  aggr (MSetVal x n) lacc racc = lacc . f n x . racc

toList :: (Ord a)  $\Rightarrow$  Set a  $\rightarrow$  [a]
toList = fold (ntimes (:)) []

ntimes :: (a  $\rightarrow$  b  $\rightarrow$  b)  $\rightarrow$  Int  $\rightarrow$  a  $\rightarrow$  b  $\rightarrow$  b
ntimes f n x y
| n > 0      = f x (ntimes f (n-1) x y)
| n == 0     = y
| otherwise   = error "MultiSets.ntimes:_negative_repetitions"

mapMonotone :: (Ord a, Ord b)  $\Rightarrow$  (a  $\rightarrow$  b)  $\rightarrow$  Set a  $\rightarrow$  Set b
mapMonotone f (MakeSet t) = MakeSet (RBT.mapMonotone f' t)
 $\text{where}$ 
  f' (MSetVal x n) = MSetVal (f x) n

map :: (Ord a, Ord b)  $\Rightarrow$  (a  $\rightarrow$  b)  $\rightarrow$  Set a  $\rightarrow$  Set b
map f (MakeSet t) = MakeSet (RBT.map f' t)
 $\text{where}$ 
  f' (MSetVal x n) = MSetVal (f x) n

union :: (Ord a)  $\Rightarrow$  Set a  $\rightarrow$  Set a  $\rightarrow$  Set a
union (MakeSet t1) (MakeSet t2) = MakeSet (RBT.join t2 t1)

unions :: (Ord a)  $\Rightarrow$  [Set a]  $\rightarrow$  Set a
unions = foldr union empty

intersection :: (Ord a)  $\Rightarrow$  Set a  $\rightarrow$  Set a  $\rightarrow$  Set a
intersection (MakeSet t1) (MakeSet t2) = MakeSet (RBT.meet t1 t2)

intersections :: (Ord a)  $\Rightarrow$  [Set a]  $\rightarrow$  Set a
intersections [] = empty
intersections xs = foldr1 intersection xs

delete :: Ord a  $\Rightarrow$  Int  $\rightarrow$  a  $\rightarrow$  Set a  $\rightarrow$  Set a
delete n x (MakeSet t) = MakeSet (del n x t)

del :: (Ord a)  $\Rightarrow$  Int  $\rightarrow$  a  $\rightarrow$  RBT (Val a)  $\rightarrow$  RBT (Val a)
del n x t
| m > 0      = t1
| otherwise   = t2
 $\text{where}$ 
  t1 = RBT.update (MSetVal x (-n)) t
  (MSetVal _ m) = head (RBT.lookup (MSetVal x (error "MultiSetsCompact.del:_internal_error"))) t1)
  t2 = RBT.delete (MSetVal x m) t1

difference :: (Ord a)  $\Rightarrow$  Set a  $\rightarrow$  Set a  $\rightarrow$  Set a
difference (MakeSet t1) (MakeSet t2) = MakeSet (RBT.fold aggr id t2 t1)
 $\text{where}$ 
  — aggr :: (Ord a)  $\Rightarrow$  Val a  $\rightarrow$  (RBT (Val a)  $\rightarrow$  RBT (Val a))  $\rightarrow$  (RBT (Val a)
  )  $\rightarrow$  RBT (Val a)  $\rightarrow$  (RBT (Val a)  $\rightarrow$  RBT (Val a))
  aggr (MSetVal x n) lacc racc = lacc . del n x . racc

```

```

infixl 9 \\
(\\) :: (Ord a) => Set a -> Set a -> Set a
(\\) = difference

filter :: Ord a => (a -> Bool) -> Set a -> Set a
filter p = fold insert' empty
  where
    insert' n x set@(MakeSet t) = if p x then MakeSet (RBT.update (MSetVal x n) t) else set

findMin :: Ord a => Set a -> Maybe a
findMin (MakeSet t) = fmap cnv $ RBT.findMin t
  where cnv (MSetVal x _) = x

findMax :: Ord a => Set a -> Maybe a
findMax (MakeSet t) = fmap cnv $ RBT.findMax t
  where cnv (MSetVal x _) = x

isSubsetOf :: Ord a => Set a -> Set a -> Bool
x `isSubsetOf` y = isEmpty (x \\ y)

isProperSubsetOf :: Ord a => Set a -> Set a -> Bool
x `isProperSubsetOf` y = x `isSubsetOf` y && (not $ isEmpty $ y \\ x)

— Not exported functions

sum :: (Num a, Ord a) => Set a -> a
sum = fold (ntimes (+)) 0

```

4.4 Tables.hs

Con poco sforzo si possono implementare Tabelle Associative da **a** a **b**, che sono poi funzioni da **a** in **b**, che andiamo a mantenere estensionalmente. Qui la cosa interessante è la **lookup** che deve restituire **Maybe b** invece di [b].

```

module Tables(Table,
  empty,
  filter,
  findMax,
  findMin,
  fold,
  fromList,
  isEmpty,
  lookup,
  map,
  mapMonotone,
  merge,
  merges,
  remove,
  size,
  toList,
  update) where

import qualified RedBlackTrees as RBT
import RedBlackTrees(RBT, Ord')
import Prelude hiding (
  filter,
  lookup,
  map)

```

```

data (Ord a) => Val a b = TableValue a b

instance (Ord a) => Eq (Val a b)
  where
    (TableValue k1 _) == (TableValue k2 _) = k1 == k2

instance (Ord a) => Ord (Val a b)
  where
    compare (TableValue k1 _) (TableValue k2 _) = compare k1 k2

instance (Ord a) => Ord' (Val a b)

instance (Ord a, Show a, Show b) => Show (Val a b)
  where
    showsPrec p (TableValue k v) = shows k . ("->" ++) . shows v

instance (Ord a, Read a, Read b) => Read (Val a b)
  where
    readsPrec p ts = [ (TableValue k v, ws) | (k, us) <- reads ts,
                        ("->", vs) <- lex us,
                        (v, ws) <- reads vs ]

newtype Table a b = Table (RBT (Val a b))

instance (Ord a, Eq b) => Eq (Table a b)
  where
    x == y = toList x == toList y

instance (Ord a, Show a, Show b) => Show (Table a b)
  where
    showsPrec _ (Table t) = ('<':) . (RBT.fold aggr id t) . (end:)
      where
        end = '>'

      — aggr :: Show a => ShowS -> ShowS -> ShowS
      aggr x lacc racc = lacc . shows x . comma racc

      — comma :: ShowS -> ShowS
      comma shws xs = if head ys == end then ys else (',':ys)
      where ys = shws xs

instance (Ord a, Read a, Read b) => Read (Table a b)
  where
    readsPrec _ = readsTable
    where
      readsTable ts = [ (Table t, vs) | ("<", us) <- lex ts,
                           (t, vs) <- readl us]

      readl ts = [ (RBT.empty, us) | (">", us) <- lex ts ] ++
                  [ (RBT.update x s, vs) | (x, us) <- reads ts,
                    (s, vs) <- readl' us]

      readl' ts = [ (RBT.empty, us) | (">", us) <- lex ts ] ++
                  [ (RBT.update x s, ws) | (",", us) <- lex ts,
                    (x, ws) <- reads us,
                    (s, ws) <- readl' ws]

— Exported functions

```

```

empty :: Ord a => Table a b
empty = Table RBT.empty

isEmpty :: (Ord a) => Table a b -> Bool
isEmpty (Table t) = RBT.isEmpty t

lookup :: (Ord a) => a -> Table a b -> Maybe b
lookup k (Table t) = cnv asslist
  where
    asslist = RBT.lookup (TableValue k (error "Table.lookup:_RBT.lookup_"
                                              internal_error)) t
    cnv [] = Nothing
    cnv [TableValue k' v]
      | k == k' = Just v
      | otherwise = error "Table.lookup:_lookup_mismatch"
    cnv _ = error "Table.lookup:_non-deterministic_lookup"

size :: Ord a => Table a b -> Integer
size (Table t) = RBT.fold count 0 t
  where
    count _ y z = 1+y+z

update :: (Ord a) => (a,b) -> Table a b -> Table a b
update (k,v) (Table t) = Table (RBT.update (TableValue k v) t)

fromList :: (Ord a) => [(a,b)] -> Table a b
fromList = Table . (foldl update' RBT.empty)
  where
    update' t (k,v) = RBT.update (TableValue k v) t

fold :: (Ord a) => ((a,b) -> c -> c) -> c -> Table a b -> c
fold f z (Table t) = RBT.fold aggr id t z
  where
    aggr (TableValue k v) lacc racc = lacc . f (k,v) . racc

toList :: (Ord a) => Table a b -> [(a,b)]
toList = fold (:) []

mapMonotone :: (Ord a, Ord c) => ((a,b) -> (c,d)) -> Table a b -> Table c d
mapMonotone f (Table t) = Table (RBT.mapMonotone f' t)
  where
    f' (TableValue k v) = TableValue k' v'
    where
      (k',v') = f (k,v)

map :: (Ord a, Ord c) => ((a,b) -> (c,d)) -> Table a b -> Table c d
map f (Table t) = Table (RBT.map f' t)
  where
    f' (TableValue k v) = TableValue k' v'
    where
      (k',v') = f (k,v)

merge :: (Ord a) => Table a b -> Table a b -> Table a b
merge (Table t1) (Table t2) = Table (RBT.join t1 t2)

merges :: (Ord a) => [Table a b] -> Table a b
merges = foldr merge empty

```

```

remove :: Ord a => a -> Table a b -> Table a b
remove k (Table t) = Table (RBT.delete (TableValue k (error "Table.del: internal_error")) t)

filter :: Ord a => (a -> Bool) -> Table a b -> Table a b
filter p = fold insert' empty
  where
    insert' (k,v) set@(Table t) = if p k then Table (RBT.update (TableValue k v) t) else set

findMin :: Ord a => Table a b -> Maybe a
findMin (Table t) = case RBT.findMin t of
  Just (TableValue k _) -> Just k
  Nothing                 -> Nothing

findMax :: Ord a => Table a b -> Maybe a
findMax (Table t) = case RBT.findMax t of
  Just (TableValue k _) -> Just k
  Nothing                 -> Nothing

```

— Not exported functions